

SELBSTANSAUGENDE SCHMUTZWASSERPUMPEN

LEISTUNGEN

Pumpentyp	Anschluss [Zoll]	[mm]	Feststoff - Ø [mm]	Q [m³/h]	H [m]	Motorstärke [kW]	Laufrad [mm]
2.900 1/min							
S 40	1 1/2"	40	20	20 / 13 / 05	05 / 10 / 15	1,1	110
S 45	1 1/2"	40	14	22 / 14 / 05	10 / 20 / 30	2,2	172
S 45-4	1 1/2"	40	12	22 / 16 / 10	25 / 30 / 35	4,0	172
S 50	2"	50	25	40 / 30 / 13	05 / 10 / 15	2,2	120
S 60	2"	50	17	42 / 30 / 14	10 / 20 / 30	4,0	172
S 63	2"	50	22	45 / 28 / 18	30 / 40 / 45	7,5	193
S 68	2"	50	25	50 / 39 / 21	35 / 45 / 55	11,0	220
S 80	3"	80	32	80 / 62 / 20	05 / 10 / 20	4,0	138
S 83	3"	80	27	80 / 57 / 20	15 / 25 / 35	7,5	172
S 88	3"	80	35	97 / 80 / 30	25 / 35 / 50	15,0	218
S 100	4"	100	37	120 / 95 / 25	10 / 15 / 25	11,0	158
S 108	4"	100	35	135 / 105 / 65	25 / 35 / 45	18,5	210
1.450 1/min							
S 65	2"	50	25	40 / 28 / 10	05 / 10 / 15	2,2	220
S 85	3"	80	40	80 / 62 / 20	05 / 10 / 15	4,0	220
S 91	3"	80	37	112 / 90 / 25	10 / 15 / 25	7,5	280
S 105	4"	100	45	140 / 100 / 50	05 / 10 / 15	5,5	220
S 121	4"	100	45	178 / 100 / 50	10 / 20 / 25	11,0	280
S 150	6"	150	50	260 / 180 / 80	05 / 10 / 15	11,0	220
S 161	6"	150	54	290 / 220 / 100	10 / 15 / 20	18,5	280
S 180	6"	150	40	320 / 250 / 160	20 / 25 / 30	30,0	358
S 201	8"	200	57	500 / 430 / 300	05 / 10 / 15	22,0	280
S 230	8"	200	72	630 / 550 / 250	20 / 25 / 35	55,0	358
960 1/min							
S 170	6"	150	54	300 / 240 / 120	05 / 10 / 15	11,0	352
S 220	8"	200	72	530 / 420 / 200	05 / 10 / 15	18,5	358